

strapex

SMG 10/15/25

High performance machines for plastic strapping

NEW



SMG 10/15



SMG 25



New technology
allows use of thin or
narrow strap



Save time and money with 5 mm plastic strap!

SMG 10/15/25

For small to large packages


5 Highlights

- Up to 70 cycles per minute
- Touch Panel: Strap tension easily adjustable
- Simple technology, few moving parts
- Constant strap tension for various products
- Simple coil change

Cost effective

- High availability
- Use of 5 mm PP strap with SMG 10 – the alternative to 9/12 mm strap
- Use of thin PP straps
- Maintenance-friendly


Strapex advantage



Machine, strap and after-sales service as a total package

User friendly


- Plug & Play: Very easy handling
- Mobile, ready to use anywhere
- Adjustable working height
- All operating functions using foot pedal



Strap tension easily adjustable with press button



Simple coil change



Easily accessible



Maintenance without tools



Robust, compact design

Options




Second foot pedal for operation on both sides



Cycle start triggered by photocell



Roller table for easy handling of heavy parcels



Bundle stops for precise positioning of loose packages

Further options

- **CT-Version (Cold and Tropic Environment)**
- **Foot switch with protection cover**
- **Hold down device** for compressing loose packages
- **Interface** for integration into existing production plants

Technical data	SMG 10	SMG 15	SMG 25
Dispenser position	Integrated	Integrated	Side mounted
Performance per minute	70 cycles	65 cycles	60 cycles
Arch dimensions (width x height)			
– 500 x 400 mm	5/6 mm		
– 650 x 500 mm	5/6 mm	9/12 mm	
– 850 x 650 mm			9/12 mm
– 850 x 850 mm			9/12 mm
– 1250 x 500 mm			9/12 mm
– 1250 x 850 mm			9/12 mm
– 1550 x 500 mm			9/12 mm
Working height	820–930 mm	820–930 mm	820–930 mm
– Option			670–830 mm
Electrical supply	230 V, 50 Hz	230 V, 50 Hz	230 V, 50 Hz
Strap tension, up to	300 N	450 N	450 N
Seal	Heat seal	Heat seal	Heat seal
Weight	170 kg	170 kg	190 kg
Plastic strap (PP)			
Width 5 mm	372.605.585		
9 mm		371.609.555	371.609.555
12 mm		371.612.540	371.612.540
Strap coil, inside/outside Ø	200/430 mm	200/430 mm	200/430 mm
Packages			
Min. width / Max. weight	100 mm / 35 kg	100 mm / 35 kg	100 mm / 35 kg

U.K.
Strapex
Unit 50
Empire Industrial Park
Empire Close
Aldridge, Walsall, WS9 8UQ
Phone +44 1922 742 500
Fax +44 1922 742 501

Denmark
ApS Strapex
Literbuen 9
2740 Skovlunde
Phone +45 44 85 06 00
Fax +45 44 84 94 22

Holland
Strapex Nederland B.V.
Sterrebaan 10
3542 DK Utrecht
Phone +31 30 24 80 311
Fax +31 30 24 11 654

USA
Acme
An ITW Company
501 W. Lake Street, Suite 105
Elmhurst, IL 60126
Phone 630-589-5100
Fax 630-589-5101

Australia
IWD Strapping Sales Pty Ltd.
P.O. Box 215
Melbourne Vic 3001
Phone 1 800 779 380
Fax 1 800 779 583

India
Strapex India Limited
506, Center Point, J.B. Nagar
Andheri-Kurla Road, Andheri (E)
Mumbai - 400 059
Phone +91-22-66400204/05
Fax +91-22-28252932